

imageCLASS
MF756Cx II
MF752Cdw II

Canon
Delighting You Always



A class of **Excellence**

Bring Ideas to Life in Vivid Colours.

Empower Your Business with the imageCLASS MF750 II Series. Boost productivity with advanced features, an intuitive interface, and robust security—all designed to keep your workflow smooth and efficient. Seamlessly integrating into any workspace, the MF750 II Series delivers vibrant colour where it counts and powerful performance where it matters most.

UP TO
33 PPM
(A4)
FAST PRINT
SPEED

UP TO
100 IPM
(A4)
DUPLEX
SCAN

V² COLOUR


APPLICATION
LIBRARY

MONO
UP TO **7,600**
PAGES
HIGH-YIELD
CARTRIDGE

COLOUR
UP TO **5,500**
PAGES
HIGH-YIELD
CARTRIDGE



INCREASED PRODUCTIVITY

Boost productivity with quick first print out time and single pass duplex scan—perfect for handling documents efficiently without slowing down your workflow.



CLOUD SCANNING AND PRINTING

Skip blank pages* for cleaner files. Print from or scan to third party cloud storage for seamless collaboration.

*applicable for scanning only



CUSTOMISE YOUR WORKFLOW

Streamline routine tasks with personalised shortcuts using the Application Library feature. Easily rearrange them on the Home screen to suit your workflow.



SECURITY ASSURANCE

Enjoy peace of mind with enhanced security features that verify system integrity at startup and protect against sniffing, spoofing, and tampering.

Business Can Be Simple

SPECIFICATIONS/ImageCLASS			MF756Cx II		MF752Cdw II	
			Print, Scan, Copy, Fax		Print, Scan, Copy	
PRINT	Printing Method		Colour Laser Beam Printing			
	Print Speed	A4 ¹	33 ppm (mono) / 33 ppm (colour)			
		Letter ²¹	35 ppm (mono) / 35 ppm (colour)			
		2-Sided, A4	29 ipm (mono) / 29 ipm (colour)			
	Print Resolution		600 x 600 dpi			
	Print Quality with Image Refinement Technology		1,200 x 1,200 dpi (equivalent)			
	Warm-Up Time (From Power On)		14 sec or less			
	First Print Out Time (FPOT) (Approx.) ²	A4	71 sec (mono) / 71 sec (colour)			
	Print Language		UFR II, PCL 6, Adobe® PostScript® 3™		UFR II, PCL 6	
	Auto Duplex Print		Yes			
Print Margins		Top/Bottom/Left/Right margin: 5 mm Top/Bottom/Left/Right margin: 10 mm (Envelope)				
Supported File Format for USB Direct Print		JPEG, TIFF, PDF				
COPY	Copy Speed	A4	33 ppm (mono) / 33 ppm (colour)			
	Copy Resolution		up to 600 x 600 dpi			
	First Copy Out Time (FCOT) (Approx.) Platen Glass	A4	8.3 sec (mono) / 9.4 sec (colour)			
	First Copy Out Time (FCOT) (Approx.) ADF	A4	7.6 sec (mono) / 8.8 sec (colour)			
	Reduce/Enlargement		25-400% in 1% increments			
	Copy Features		Collate 2 on 1, 4 on 1, ID Card Copy, Passport Copy, 2-sided originals			
SCAN	Scan Resolution	Optical	Up to 600 x 600 dpi			
		Driver Enhanced	Up to 9,600 x 9,600 dpi			
	Scan Type		Colour Contact Image Sensor			
	Maximum Scan Size	Platen Glass	Up to 216 x 297 mm			
		ADF	Up to 216 x 356 mm			
	Scan Speed ³	Platen Glass	1.8 sec (mono) / 1.9 sec (colour)			
		ADF	(A4) 1-Sided: 50 ipm (mono) / 40 ipm (colour) (A4) 2-Sided: 100 ipm (mono) / 80 ipm (colour)			
	Colour Depth		24-bit			
	Pull Scan		Yes, USB and Network			
	Push Scan (Scan To PC) with MF Scan Utility		Yes, USB and Network			
SEND	Scan To Cloud		MF Scan Utility			
	SEND Method		SMB, Email, FTP, iFAX Simple		SMB, Email, FTP	
	Colour Mode		Full Colour, Greyscale, Monochrome			
	Scan Resolution		300 x 600 dpi			
File Format		JPEG (single page), TIFF, PDF, Compact PDF, PDF (OCR)				
FAX	Modem Speed		Up to 33.6 Kbps (Up to 3 sec/page)		-	
	Fax Resolution		Up to 400 x 400 dpi		-	
	Compression Method		MH, MR, MMR, JBIG		-	
	Memory Capacity ⁴		Up to 90 jobs		-	
	Speed Dials		Up to 281 dials		-	
	Group Dials / Destinations		Up to 299 dials		-	
	Sequential Broadcast		310 destinations		-	
	Receive Mode		Fax Only, Fax/tel Auto Switch, Answer Mode, Manual		-	
	Memory Backup		Permanent Fax Memory Backup		-	
Fax features		Fax Forwarding, Remote Reception, PC Fax (Transmit Only), DRPD, ECM, Auto Redial, Fax, Activity Reports, Fax Activity Result Reports, Fax Activity Management Reports		-		

¹ Print speed is measured based on internal testing using A4/Letter size paper printed with 100% print ratio to original on one-sided paper. Internal testing involved continuously printing the same one page of content on plain paper. Print speed may vary depending on paper type, paper size or paper feeding direction.
² First print out time is measured based on internal test procedure and may vary. When the printer is in the ready state, this is the time from receiving the print instruction from the controller to printing one sheet and finishing paper ejection.
³ Scan resolution 300 x 300 dpi.

SPECIFICATIONS/ImageCLASS			MF756Cx II	MF752Cdw II
			Print, Scan, Copy, Fax	Print, Scan, Copy
PAPER HANDLING	Input tray Capacity (Plain Paper, 80 g/m ²)	Standard	Cassette	250 sheets
			Multi Purpose tray	50 sheets
			ADF	50 sheets Duplex, Single Pass
		Optional	Paper Feeder	550 sheets
			Maximum	850 sheets (Cassette + 1 Paper Feeder)
	Output Tray Capacity (Plain Paper, 80 g/m ²)		150 sheets	
	Media Size		Cassette	A4, A5, A6, Legal, Letter, Foolscap, Indian Legal, Envelope (COM10, Monarch, DL, C5) Custom (Min. 98.0 x 148.0 mm to Max. 216.0 x 356.0 mm)
			Paper Feeder	A4, A5, A6, Legal, Letter, Foolscap, Indian Legal, Custom (Min. 100.0 x 148.0 mm to Max. 216.0 x 356.0 mm)
			Multi Purpose Tray	A4, A5, A6, Legal, Letter, Foolscap, Indian Legal, Index Card, Envelope (COM10, Monarch, DL, C5) Custom (Min. 76.0 x 127.0 mm to Max. 216.0 x 356.0 mm)
			ADF	A4, A5, A6, Letter, Legal (min. 148 x 105 mm to max. 216 x 356 mm) Business card: 48 x 85 mm
			2-Sided Printing	A4, A5, Legal, letter, Foolscap, indian Legal, Custom (min. 148.0 x 148.0 mm to max. 216 x 356.0 mm)
	Media type		Plain Paper, Recycled paper, Colour Paper, Bond Paper	
	Media Weight		Cassette/Paper Feeder	60—200 g/m ²
			Multi Purpose Tray	60—200 g/m ²
			ADF	50—105 g/m ² (Business Card: 80 to 209 g/m ²)
CONNECTIVITY & SOFTWARE	Standard Interface	Wired	USB 2.0, 10Base-T/100Base-TX/1000Base-T	
		Wireless	Wi-Fi 802.11b/g/n (Infrastructure Mode, Access Point, WPS)	
	Network Protocol	Print	LPD, RAW, IPP, IPPS, WSD-Print (IPv4, IPv6)	LPD, RAW, IPP, WSD-Print (IPv4, IPv6)
		Scan	Email, SMB, WSD-Scan (IPv4, IPv6), FTP, OAuth 2.0	
		Application	mDNS, DHCP, Auto IP (IPv4), DHCPv6 (IPv6)	
		Management	SNMPv3 (IPv4, IPv6), HTTP/HTTPS, SNMP	
	Network Security	Wired	IP/Mac Address Filtering, HTTPS, SNMPv3, IEEE802.1X, IPsec, TLS 1.3	
		Wireless	Infrastructure Mode: WPA-PSK(AES), WPA2-PSK(AES), WPA3-SAE(AES), WPA-EAP(AES), WPA2-EAP(AES), WPA3-EAP(AES) Access Point Mode: WPA2-PSK(AES), WPA3-SAE(AES)	
	Mobile Solution		Canon PRINT app, AirPrint®, Mopria® Print Service, Microsoft Universal Print	
	Compatible operating Systems ⁵		Windows®, Windows Server®, macOS®, Linux, ChromeOS™	
	Other features		Department ID, Secure Print, Skip Blank Page, Application Library	
GENERAL	Available Software		Printer Driver, Fax Driver, Scanner Driver, MF Scan Utility, Toner Status	Printer Driver, Scanner Driver, MF Scan Utility, Toner Status
	Device Memory		1GB	
	Storage (eMMC)		2GB	
	Display		5" LCD Touchscreen	
	Power Requirements		AC 220 – 240 V, 50/60 Hz	
	Power Consumption (Approx)	Operation	700 W (max. 1380 W)	
		Standby	24 W	
		Sleep	1 W	
	Operating Environment	Temperature	10 – 30°C	
		Humidity	20 – 80% RH (no condensation)	
OPTIONAL	Monthly Duty Cycle ⁶		50,000 pages	
	Dimensions (W x D x H)		425 x 461 x 430 mm	
	Weight ⁷ (Approx.)		21.95 kg	21.71 kg
	Toner Cartridge ⁸	Standard	Cartridge 069 BK: 2,100 pages (bundled: 2,100 pages) Cartridge 069 CMY: 1,900 pages (bundled: 1,100 pages)	
		High	Cartridge 069H BK: 7,600 pages Cartridge 069H CMY: 5,500 pages	
	Paper Feeder		Paper Feeder PF-K1 (550 sheets)	
	Barcode Printing		Barcode Printing Kit-E1E	-

⁴ Based on ITU-T #1 Chart (standard mode).
⁵ The latest drivers for Windows, Windows Server, Mac OS and Linux can be downloaded from the <https://asia.canon/en/support> website when available.
⁶ Monthly Duty Cycle value provides a means of comparison for product robustness in relation to other Canon laser printer devices, and does not refer to actual maximum image output per month.
⁷ Excluding toner cartridge.
⁸ Toner cartridge yield is in accordance with ISO/IEC 19798.



SOUTH AND SOUTHEAST ASIA REGIONAL HEADQUARTERS CANON SINGAPORE PTE. LTD.

1 Fusionopolis Place, #14-10 Galaxis, Singapore 138522
 Tel : 65-6799-8888 | Fax : 65-6799-8882 | <https://asia.canon>

DEALER'S STAMP

This document is for general information only and contents are subject to change without notice. Errors and omissions excepted. Weights and dimensions are approximates. Options, name and availability may vary by regions. Nothing in this document should be construed as a warranty. We expressly disclaim any liability or contractual obligations in connection with this document. Trademarks belong to their respective owners.