

imageCLASS
MF667Cx
MF664Cdw
MF662Cdw

Canon
Delighting You Always



A class of **Excellence**

Brilliant Ideas In Vivid Colour

Create impactful visuals with colours. Whether you're printing key proposals or archiving important documents, the imageCLASS MF660 series keeps your workflow smooth and efficient. Equipped with productivity-focused features, intuitive interface, and robust security features, it's a smart choice for the bustling office.

**UP TO
25 PPM
(A4)**
FAST PRINT
SPEED

**UP TO
100 IPM
(A4)**
DUPLEX
SCAN

V² COLOUR

**APPLICATION
LIBRARY**

**MONO
UP TO 3,500
PAGES**
HIGH-YIELD CARTRIDGES

**COLOUR
UP TO 2,500
PAGES**
HIGH-YIELD CARTRIDGES



COMPACT AND FAST

With a first print out time of 10.5 seconds and print speed of up to 25ppm, it's high in performance while compact enough to fit neatly into tight space or countertop.



INCREASE PRODUCTIVITY

Efficiently scan two-sided originals with the Duplex Auto Document Feeder (DADF)*, which includes a Skip Blank Page feature and supports scanning of name cards with up to 209 g/m².

* Two-sided scanning is only applicable for MF667Cx.



EASY USABILITY

The 5-inch Touch Screen LCD makes navigation seamless and intuitive. With Application Library, frequently used tasks can be streamlined into custom shortcuts for efficient workflow.



ROBUST SECURITY FOR A PEACE OF MIND

Built-in security features defend against unauthorised access and maintain the integrity of your information, protecting it from sniffing, spoofing, and tampering.

Business Can Be Simple

SPECIFICATIONS

MF667Cx | MF664Cdw | MF662Cdw

PRINT	Printing Method		Colour Laser Beam Printing		
	Print Speed	A4 ^{*1} (mono/colour)	25 / 25 ppm		
		Letter (mono/colour)	26 / 26 ppm		
		2-Sided, A4 (mono/colour)	15 / 15 ipm		
	Print Resolution		600 x 600 dpi		
	Print Quality with Image Refinement Technology		1,200 x 1,200 dpi (equivalent)		
	Warm-Up Time (From Power On)		13 sec or less		
	First Print Out Time (FPOT) (Approx.) ^{*2}	A4 (mono/colour)	10.4 / 10.5 sec		
	Print Language		UFR II, PCL 6, Adobe® PostScript® 3™	UFR II, PCL 6	UFR II
	Auto Duplex Print		Yes		
Print Margins		Top/Bottom/Left/Right margin: 5 mm Top/Bottom/Left/Right margin: 10 mm (Envelope)			
Supported File Format for USB Direct Print		JPEG, TIFF, PDF			
COPY	Copy Speed	A4 (mono/colour)	25 / 25 ppm		
	Copy Resolution		Up to 600 x 600 dpi		
	First Copy Out Time (FCOT) (Approx.) Platen Glass	A4 (mono/colour)	11.0 / 11.2 sec		
	First Copy Out Time (FCOT) (Approx.) ADF	A4 (mono/colour)	10.5 / 10.6 sec	-	
	Reduce / Enlargement		25 - 400% in 1% increments		
	Copy Features		Collate, 2 on 1, 4 on 1, ID Card Copy, Passport Copy		
	SCAN	Scan Resolution	Optical Driver Enhanced	Up to 600 x 600 dpi Up to 9,600 x 9,600 dpi	
Scan Type		Colour Contact Image Sensor			
Maximum Scan Size		Platen Glass	Up to 216 x 297 mm		
		Auto Document Feeder	Up to 216 x 356 mm		-
Scan Speed ^{*3}		Platen Glass, A4 (mono/colour)	1.8 / 1.9 sec		
		Auto Document Feeder, A4 (mono/colour)	1-Sided: 50 / 40 ipm 2-Sided: 100 / 80 ipm	1-Sided: 50 / 40 ipm	-
Colour Depth		24-bit			
Pull Scan		Yes, USB and Network			
Push Scan (Scan To PC) with MF Scan Utility		Yes, USB and Network			
Scan To Cloud		MF Scan Utility			
Scan Driver Compatibility		TWAIN, WIA			
SEND	Send Method		SMB, Email, FTP, iFAX Simple	SMB, Email, FTP	
	Colour Mode		Full Colour, Greyscale, Monochrome		
	Scan Resolution		300 x 600 dpi		
	File Format		JPEG (single page), TIFF, PDF, Compact PDF, PDF (OCR)		
FAX	Modem Speed		Up to 33.6 Kbps (Up to 3 sec/page)	-	
	Fax Resolution		Up to 400 x 400 dpi	-	
	Compression Method		MH, MR, MMR, JBIG	-	
	Memory Capacity ^{*4}		Up to 90 jobs	-	
	Speed Dials		Up to 281 dials	-	
	Group Dials / Destinations		Up to 299 dials	-	
	Sequential Broadcast		310 destinations	-	
	Receive Mode		Fax only, Fax/Tel Auto Switch, Answer Mode, Manual	-	
	Memory Backup		Permanent fax memory backup	-	
	Fax Features		Fax Forwarding, Remote Reception, PC Fax (Transmit only) DRPD, ECM, Auto Redial, Fax Activity Reports, Fax Activity Result Reports, Fax Activity Management Reports	-	

MF667Cx | MF664Cdw | MF662Cdw

PAPER HANDLING	Input Tray Capacity (Plain paper, 80 g/m ²)	Cassette	250 sheets		
		Manual Feed Slot	1 sheet		
		Auto Document Feeder	50 sheets Duplex, Single Pass	50 sheets	-
		Maximum	251 sheets (Cassette + 1 Manual Feed Slot)		
	Output Tray Capacity (Plain paper, 80 g/m ²)		100 sheets		
	Media Size	Cassette	A4, A5, A6, Legal, Letter, Foolscap, Indian Legal, Index Card, Postcard, Envelope (COM10, Monarch, DL, C5), Custom (min. 76.2 x 127 mm to max. 216 x 355.6 mm)		
		Manual Feed Slot	A4, A5, A6, Legal, Letter, Foolscap, Indian Legal, Index Card, Postcard, Envelope (COM10, Monarch, DL, C5), Custom (min. 76.2 x 127 mm to max. 216 x 355.6 mm)		
		Auto Document Feeder	A4, A5, A6, Letter, Legal (min. 148 x 105 mm to max. 216 x 356 mm), Business Card: 48 x 85 mm		-
		2-Sided Printing	A4, Legal, Letter, Foolscap, Indian Legal, Custom (min. 182 x 257.0 mm to max. 216 x 355.6 mm)		
	Media Type		Plain Paper, Recycled Paper, Colour Paper, Bond Paper		
Media Weight	Cassette	60 - 200 g/m ²			
	Manual Feed Slot	60 - 200 g/m ²			
	Auto Document Feeder	50 - 105 g/m ² (Business Card: 80 to 209 g/m ²)	-		
CONNECTIVITY & SOFTWARE	Standard Interface	Wired	USB 2.0, 10Base-T/100Base-TX/1000Base-T		
		Wireless	Wi-Fi 802.11b/g/n (Infrastructure Mode, WPS, Direct Connection)		
	Network Protocol	Print	LPD, RAW, IPP, IPPS, WSD-Print (IPv4, IPv6)		
		Scan	Email, SMB, WSD-Scan (IPv4, IPv6), FTP, OAuth 2.0		
		TCP/IP			
		Application Services	mDNS, DHCP, Auto IP (IPv4), DHCPv6 (IPv6)		
	Network Security	Management	SNMP v3 (IPv4, IPv6), HTTP/HTTPS, SNTp		
		Wired	IP/Mac Address Filtering, HTTPS, SNMPv3, IEEE802.1X, IPsec, TLS 1.3		
		Wireless	Infrastructure Mode: WPA-PSK(AES), WPA2-PSK(AES), WPA3-SAE(AES), WPA-EAP(AES), WPA2-EAP(AES), WPA3-EAP(AES) Access Point Mode: WPA2-PSK(AES), WPA3-SAE(AES)		
	Mobile Solution		Canon PRINT app, AirPrint®, Mopria® Print Service, Microsoft Universal Print		
	Compatible Operating Systems ^{*5}		Windows®, Windows Server®, macOS®, Linux, ChromeOS™		
	Other Features		Department ID, Secure Print, Skip Blank Page, Application Library	Department ID, Secure Print, Application Library	
	Available Software		Printer Driver, Scanner Driver, MF Scan Utility, Toner Status, Fax Driver (only MF667Cx)		
GENERAL	Device Memory		1 GB		
	Storage (eMMC)		2 GB		
	Display		5" LCD Touchscreen		
	Power Requirements		AC 220 - 240 V, 50/60 Hz		
	Power Consumption (Approx.)	Operation	580 W (max. 980 W)		
		Standby	12 W		
		Sleep	1 W		
	Operating Environment	Temperature	10 - 30°C		
	Humidity	20% - 80% RH (no condensation)			
	Monthly Duty Cycle ^{*6}		30,000 pages		
	Dimensions (W x D x H) (Approx.)		425 x 461 x 397 mm	425 x 461 x 360 mm	
	Weight ^{*7} (Approx.)		18.71 kg	16.49 kg	
	Toner Cartridge ^{*8}	Standard	Cartridge 075 BK: 1,400 pages (Bundled: 1,400 pages) Cartridge 075 C/M/Y: 1,300 pages (Bundled: 500 pages)		
		High	Cartridge 075H BK: 3,500 pages; Cartridge 075H C/M/Y: 2,500 pages		

- *1 Print speed is measured based on internal testing using A4/Letter size paper printed with 100% print ratio to original on one-sided paper. Internal testing involved continuously printing the same one page of content on plain paper. Print speed may vary depending on paper type, paper size or paper feeding direction.
- *2 First print out time is measured based on internal test procedure and may vary. When the printer is in the ready state, this is the time from receiving the print instruction from the controller to printing one sheet and finishing paper ejection.
- *3 Scan resolution 300 x 300 dpi.
- *4 Based on ITU-T #1 Chart (standard mode).
- *5 The latest drivers for Windows, Windows Server, Mac OS and Linux can be downloaded from the <https://asia.canon/en/support> website when available.
- *6 Monthly Duty Cycle value provides a means of comparison for product robustness in relation to other Canon laser printer devices, and does not refer to actual maximum image output per month.
- *7 Excluding toner cartridge.
- *8 Toner cartridge yield is in accordance with ISO/IEC 19798.



Delighting You Always

SOUTH AND SOUTHEAST ASIA REGIONAL HEADQUARTERS
CANON SINGAPORE PTE. LTD.

1 Fusionopolis Place, #14-10 Galaxis, Singapore 138522

Tel : 65-6799-8888 | Fax : 65-6799-8882 | <https://asia.canon>

DEALER'S STAMP

This document is for general information only and contents are subject to change without notice. Errors and omissions excepted. Weights and dimensions are approximates. Options, name and availability may vary by regions. Nothing in this document should be construed as a warranty. We expressly disclaim any liability or contractual obligations in connection with this document. Trademarks belong to their respective owners.